



System Simple START is a board based system. It is designed for board thickness ranging from 16-50 mm. Maximum door weight is up to 50 kg.

Simple Start features straightforward design, along with fast and easy assembly.

This system comprises of three main elements: Ball bearing bottom carriage, top guide and universal track SMART that is used as top and bottom track.


The use of track SMART significantly reduces the production cost.

This system also incorporates stopper START, made from steel. It is easily fixed to the track and prevents unwanted door drift.




CONSTRUCTION	CARRIAGE SYSTEM		FILLING	LOAD	MAX. HANDLE LENGTH	MAX. TRACK LENGTH
BOARD	TOP	Sliding guide	BOARD 16-50 mm	50 kg	-	6 m
	BOTTOM	Ball bearing carriage (load bearing)				

Track **Start**



CODE	COLOUR	LENGTH (mm)	COLLECTIVE PACKAGING	PRICED PER	NET PRICE
50481	RAW	1500	50	ITEM	
50482	RAW	2000	50	ITEM	
50483	RAW	2500	50	ITEM	
50484	RAW	3000	50	ITEM	
50485	RAW	4000	50	ITEM	
50486	RAW	6000	50	ITEM	



Top guide **Simple Start**



CODE	COLLECTIVE PACKAGING	PRICED PER	NET PRICE
10173	100	ITEM	

Bottom carriage **Simple Start**



CODE	COLLECTIVE PACKAGING	PRICED PER	NET PRICE
10172	100	ITEM	

Stopper **Simple Start**



CODE	COLLECTIVE PACKAGING	PRICED PER	NET PRICE
110174	1000	ITEM	